Each

Dart Aerospace Ltd. Tuesday, 1/8/2008 1:20:23 PM Kim Johnston **Process Sheet** : BOLT **Drawing Name** : CU-DAR001 Dart Helicopters Services Customer Job Number **Estimate Number** : 10372 : NIA Part Number : D312121 P.O. Number . D3121 REV E : 1/8/2008 S.O. No. : NA **Drawing Number** This Issue : N/A Project Number Prsht Rev. : E . : MACHINED PARTS First Issue Type **Drawing Revision** : 36608 Material Previous Run 1/31/2008 Qty: 60 Um: **Due Date** Written By Checked & Approved By 04.02.09 New issue KJ/DS Comment Est Rev:B ECN 1060 07-11-12 DD verified by:EC **Additional Product** Job Number: Description: Machine Or Operation: Seq. #: 303 HEX BAR M303H0500 1.0 Comment: Qtv.: 0.0417 f(s)/Unit Total: 2.5020 f(s) 303 HEX BAR Material: AISI 303 SS 1/2" Hex Bar (M303H0.500) Batch: <u>MIn(o 78</u> HARDINGE CNC LATHE SMALL 2.0 Comment: HARDINGE CNC LATHE SMALL 1-Turn D3121-21 2-Identify as D3121-21 3-Deburr break all sharp edges 0.005" to 0.010" INSPECT PARTS AS THEY COME OFF MACHINE 3.0 QC2 Comment: INSPECT PARTS AS THEY COME OFF MACHINE 4.0 QC8




SECOND CHECK



Comment: SECOND CHECK

PACKAGING

PACKAGING RESOURCE #1







Comment: PACKAGING RESOURCE #1

Identify and Stock Location: 66





5.0

Dart Aerospace Ltd

	WORK ORD	ER CHANGES				
STEP	PROCEDURE CHANGE	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
			. ,			
	PAR #: Fault Category:	NCR: Yes	No DQA	1: <u>I</u>	Date:	8/01/15
		QA:	N/C Closed	ł:	_ Date: _	
	STEP	STEP PROCEDURE CHANGE	:	STEP	STEP	STEP PROCEDURE CHANGE By Date Qty Chief Eng / Prod Mgr

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
		Description of NC		Corrective Action Section E	3	Verification		
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Section C	Approval Chief Eng	Approval QC Inspector

NOTE: Date & initial all entries

Date:

Tuesday, 1/8/2008 1:20:23 PM

User:

Kim Johnston

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: BOLT

Job Number: 36668

Part Number: D312121

Job Number:



Seq. #:

Machine Or Operation:

Description:

6.0

QC21



FINAL INSPECTION/W/O RELEASE



Comment: FINAL INSPECTION/W/O RELEASE

Job Completion



U 08.01.14

Dart Ae	rospace	Ltd							
W/O:		· · · · · · · · · · · · · · · · · · ·	W	ORK ORDER CHANGES					-
DATE	STEP	PRO	PROCEDURE CHANGE		Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
Part No	:	PAR #:	Fault Cate	gory: No	CR: Yes	No DQ	A:	Date:	
					QA: N/	C Close	d:	_ Date: _	
NCR:		· V	VORK ORD	ER NON-CONFORMANC	E (NCR)			
		Description of NC		Corrective Action Section B		Verific	cation	Approval	Approval
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date		ion C	Chief Eng	QC Inspector

NOTE: Date & initial all entries

DART AEROSPACE LTD	Work Order:	36668	
Description: Bolt	Part Number:	D3121-21	
Inspection Dwg: D3121 Rev:		Page 1 of 1	

FIRST ARTICLE INSPECTION CHECKLIST

| X | First Article | Prototype

Drawing Dimension	Tolerance	Actual Dimension	Accept	Reject	Method of Inspection	Comments
0.375	+/-0.010	, 383"				
0.050 - 0.060	N/A	259"				
0.080	+/-0.010	,020"			e vinicial i is	
10-32UNF3A	N/A	10-32 unf 3	1			
		000000				
	400					
				<u>-</u>		


	10 ·				: 	
					·	

Measured by: J.F.	Audited by:	12	Prototype Approval:	N/A
Date: 08/0/1/3	Date:	8/01/13	Date:	N/A

Rev	Date	Change	Revised by	Approved
Α	04.02.27	New Issue	KJ/RF	
. В	06.03.09	Dwg Rev. updated	KJ/JLM	1
С	06.06.14	Dwg Rev. updated	KJ/JLM 🚓	




	DESIGN A DRAWN BY		DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA
	CHEC	(ED_	APPROVED	DRAWING NO. REV. E
		#		D3121 SHEET 1 OF 10
	DATE			TITLE SCALE
	07.1	1.07		BRACKET ASSEMBLY 1:2
	Α		02.04.15	NEW ISSUE
	В		03.01.16	ADD RIDGES; ADD MAT'L PROP; FIX P/N ADD -141/-143/-144/-145/-146
	С		04.02.17	ADD CLEARANCE; USE -241 BEARING
	D		06.05.17	D3121-25 CAP WAS 1.024, NOW 1.000
į	Ε		07.11.07	ADD TOLERANCE TO 0.032 (DETAIL B)



- D3121-2 D3121-2	(1)
BEARING	 LY	(1)

D3121-041 BRACKET ASSEMBLY


(REPLACES PREMIER P/N B30-23000-33)



- D3121-21 BOLT (1) D3121-241 BEARING ASSEMBLY (1) (2 PLACES)

D3121-13/-14 BRACKET D3121-043 (SHOWN) / D3121-044 (OPPOSITE) BRACKET ASSEMBLY

(REPLACES PREMIER P/N B30-23000-37/-38)



D3121-21 BOLT (1) D3121-241 BEARING ASSEMBLY (1) (2 PLACES)

D3121-15/-16 BRACKET

D3121-045 (SHOWN) / D3121-046 (OPPOSITE) BRACKET ASSEMBLY


(REPLACES PREMIER P/N B 30_{SH} 23000-35/-36)

RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER
NO. SOLOTOR

Copyright © 2002 by DART AEROSPACE LTD



DESIGN	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
CHECKED	APPROVED	DRAWING NO.	REV. E	
#	#	D3121	SHEET 2 OF 10	
DATE		TITLE	SCALE	
07.11.07		BRACKET ASSEMBLY	1:2	





Copyright © 2002 by DART AEROSPACE LTD




DESIGN	DRAWN BY	DART AEROSI HAWKESBURY, ONTA	
CHECKED	APPROVED,	DRAWING NO.	REV. E
4	-#	D3121	SHEET 3 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:1








SECTION C-C



DETAIL B: RIDGE DETAIL PARTIAL SECTION SCALE 1:20




SHOP COPY RETURN TO ENGINEERING UNCONTROLLED COPY SUBJECT TO AMENDMENT WITHOUT NOTICE

WORK ORDER 8



DESIGN	DRAWN BY	DART AEROS HAWKESBURY, ONTA	
CHECKED _	APPROVED,	DRAWING NO.	REV. E
#	-#	D3121	SHEET 4 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:1



D3121-11 BRACKET

1) MATERIAL: 17-4 SS PER AMS 5604/5643 (REF DART SPEC. M17-4-B) MIN ULTIMATE TENSILE = 150 ksi

MIN YIELD TENSILE = 100 ksi

2) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

3) ALL DIMENSIONS ARE IN INCHES

4) BREAK ALL SHARP EDGES 0.005 TO 0.015

5) ENGRAVE DART P/N & LOGO AS SHOWN

6) HOLE IN SPIGOT TO BE CONCENTRIC WITHIN 0.005

SHOP COPY RETURN TO **ENGINEERING**

UNCONTROLLED COPY

SUBJECT TO AMENDMENT WITHOUT NOTICE

WORK ORDER



DESIGN	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED	APPROVED	DRAWING NO.	REV. E
4	#	D3121	SHEET 5 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:2



a

DAVIT

D3121-13

1.220 - 1.800 -

 \bigoplus

 \bigoplus

SEE

2.63


<u></u>6\-

0.400

1.280

0.960

الـــ 0.330



D3121-13 BRACKET (SHOWN) D3121-14 BRACKET (OPPOSITE)

1) MATERIAL: 17-4 SS PER AMS 5604/5643 (REF DART SPEC. M17-4-B) MIN ULTIMATE TENSILE STRENGTH = 150 ksi

MIN YIELD TENSILE STRENGTH = 100 ksi

- 2) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 3) ALL DIMENSIONS ARE IN INCHES
- 4) BREAK ALL SHARP EDGES 0.005 TO 0.015
- 5) ENGRAVE DART P/N & LOGO AS SHOWN
- 6) HOLE IN SPIGOT TO BE CONCENTRIC WITHIN 0.005


SHOP COPY RETURN TO ENGINEERING

JNCONTROLLED COPY SUBJECT TO AMENDMENT WITHOUT NOTICE

WORK,ORDER



DESIGN	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED	APPROVED	DRAWING NO.	REV. E
#	4	D3121	SHEET 6 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:2



D3121-15 BRACKET (SHOWN) D3121-16 BRACKET (OPPOSITE)

1) MATERIAL: 17-4 SS PER AMS 5604/5643 (REF DART SPEC. M17-4-B)

MIN ULTIMATE TENSILE = 150 ksi MIN YIELD TENSILE = 100 ksi

2) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

3) ALL DIMENSIONS ARE IN INCHES

4) BREAK ALL SHARP EDGES 0.005 TO 0.015

5) ENGRAVE DART P/N AND LOGO AS SHOWN

6) HOLE IN SPIGOT TO BE CONCENTRIC WITHIN 0.005

SHOP COPY RETURN TO ENGINEERING


UNCONTROLLED COP SUBJECT TO AMENDMEN WITHOUT NOTICE

NO. SOO GE

Copyright @ 2002 by DART AEROSPACE LTD



DESIGN 4	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED _	APPROVED	DRAWING NO.	REV. E
4H		D3121	SHEET 7 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:2



D3121-111 BRACKET

- 1) REPLACES PREMIER P/N B32-23001-11
- 2) MATERIAL: 17-4 SS PER AMS 5604/5643 (REF DART SPEC. M17-4-B)
 MIN ULTIMATE TENSILE = 150 ksi

MIN YIELD TENSILE = 100 ksi

- 3) TOLERANCES ARE PER DART QSI 018 UNLESS OTHEWISE NOTED
- 4) ALL DIMENSIONS ARE IN INCHES
- 5) BREAK ALL SHARP EDGES 0.005 TO 0.015
- 6) ENGRAVE DART P/N & LOGO IN AREAS SHOWN
- 7) HOLE IN SPIGOT TO BE CONCENTRIC WITHIN 0.005

SHOP COPY

RETURN TO


ENGINEERING
INCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE

WORK ORDERS

Copyright © 2002 by DART AEROSPACE LTD




DESIGN	d DRAW	DA DA	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKE	APPRO	DVED DRAWING NO.	REV. I	
1 .	# -	D3121	SHEET 8 OF 10	
DATE		TITLE	SCALI	
07.11	.07	BRACKET	ASSEMBLY 1:	



Copyright © 2002 by DART AEROSPACE LTD





DESIGN DRAWN BY		DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED _	APPROVED	DRAWING NO.	REV. E
4	-#	D3121	SHEET 9 OF 10
DATE		TITLE	SCALE
07.11.07		BRACKET ASSEMBLY	1:2



Copyright © 2002 by DART AEROSPACE LTD









D3121-17 WASHER (SCALE 2:1)

- 1) REPLACES PREMIER P/N B32-23001-17
- 2) MATERIAL: AISI 303 SS ROUND BAR, ANNEALED (REF DART SPEC. M303R)
- 3) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) ALL DIMENSIONS ARE IN INCHES
- 5) BREAK ALL SHARP EDGES 0.005 TO 0.015



D3121-19 BEARING (SCALE 1:1)

- 1) POSSIBLE SUPPLIER: KING BEARING P/N 6000-2ZJ/EM FAFNIR P/N 9100KDD
- 2) ALL DIMENSIONS ARE IN INCHES



D3121-23 BEARING (SCALE 1:1)


1) POSSIBLE SUPPLIER: SKF P/N 61900-2Z OR KML P/N 6900-ZZ

ALL DIMENSIONS ARE IN INCHES

0.375 TAP 10-32 UNF-3A - 0.080 - 0.050 TO 0.060


D3121-21 BOLT (SCALE 1:1)

- 1) MATERIAL: AISI 303 SS HEX, ANNEALED (REF DART SPEC. M303H0.500)
- NONE 2) FINISH:
- 3) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) ALL DIMENSIONS ARE IN INCHES
- 5) BREAK ALL SHARP EDGES 0.005 TO 0.015



D3121-25 CAP (SCALE 1:1)

- 1) MATERIAL: DELRIN ROD, Ø1.25 (REF DART SPEC. M-DELRIN-R1.250)
- 2) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 3) ALL DIMENSIONS ARE IN INCHES



D3121-241 BEARING ASSEBLY (SCALE 1:1)

Copyright @ 2002 by DART AEROSPACE LTD